



ExaGrid

Technical Specifications

DATA SHEET

Application Support – All ExaGrid Appliances

Backup Applications, Utilities, and Methods

- Acronis Backup & Recovery
- Arcserve Backup, D2D, UDP
- BridgeHead
- Carbonite Amanda
- Commvault
- Dell EMC NetWorker
- HYCU
- IBM TSM (Spectrum Protect)
- Idera SQL Safe
- Micro Focus Data Protector
- Quest LiteSpeed, NetVault
- Quest vRanger
- Red Gate SQL Backup
- StorageCraft ShadowProtect
- Veeam Backup & Replication
- Veritas Backup Exec
- Veritas NetBackup
- Veritas System Recovery
- Zerto Offsite Backup
- POSIX-compliant TAR files
- Oracle RMAN
- SQL Dumps

Site Configurations

- Scalable from 3TB to 2PB full backup (12TB to 4.6PB raw) with 32 servers in a single system
- Hub-and-spoke architecture
- Mix and match different size/age appliance models
- ExaGrid sites (one hub and up to 15 spokes)
- Standard IP WAN connection between sites
- WAN encryption for secure data transfer
- Bandwidth throttling for WAN efficiency

Appliance Configurations

ExaGrid Model	EX3000	EX5000	EX7000 / -SEC	EX10000E / -SEC	EX13000E / -SEC	EX21000E / -SEC	EX32000E / -SEC	EX40000E / -SEC	EX63000E / -SEC
Chassis	2U	2U	2U	2U	2U	2U	3U	3U	4U
Full Backup	3TB	5TB	7TB	10TB	13TB	21TB	32TB	40TB	63TB
Disks	6	8	10	8	10	10	14	16	24
Disk Size	2TB	2TB	2TB	4TB	4TB	6TB	6TB	6TB	6TB
Memory	8 GiB	8 GiB	8 GiB	16 GiB	16 GiB	32 GiB	32 GiB	64 GiB	128 GiB
CPUs / Cores	1 CPU 4 cores					1 CPU 4 hyper-threaded cores		1 CPU 6 hyper-threaded cores	2 CPU 8 hyper-threaded cores
NIC Ports	Four 1GbE and two optional 10GbE							Four 1GbE, two 10GbE or two optional 40GbE	

All Servers: Intel processors / Enterprise SAS drives (SATA drives for EX3000, EX5000, EX7000, EX10000E, EX13000E); FIPS 140-2 Self-Encrypting SAS drives for all -SEC systems / RAID6 with hot spare / Redundant fans / Redundant power supplies / ExaGrid software / 19-inch rack-mount chassis

Regulatory Approvals

- UL/CSA 60950-1
- IEC 60950-1
- EN 60950-1
- FCC Class A
- CB Certificate
- ICES-003
- EN 55024
- EN 55022/32
- CISPR 22/32
- VCCI
- EN 61000-3-2/3
- RoHS Compliant

Environmental Requirements

	Power	Temperature	Humidity	Cooling (Operating)
ALL APPLIANCES	Frequency: 50-60 Hz / Voltage: 100-240 VAC Two NEMA5-15P to C13 US power cords, 6ft. Country kits available for international orders EX3000: 220W (1.83A @ 120VAC) EX5000 thru EX21000E: 270W (2.25A @ 120VAC) EX32000E: 375W (3.13A @ 120VAC) EX40000E: 336W (2.8A @ 120VAC) EX63000E: 500W (4.2A @ 120VAC)	10° to 35° C (50° to 95° F)	20% to 80% non-condensing	EX3000: 751 BTU/hr EX5000 thru EX21000E: 922 BTU/hr * EX32000E: 1280 BTU/hr * EX40000E: 1147 BTU/hr * EX63000E: 1705 BTU/hr * * including -SEC

United States: 350 Campus Drive | Marlborough, MA 01752 | (800) 868-6985
 United Kingdom: 200 Brook Drive | Green Park, Reading, Berkshire RG2 6UB | +44 (0) 1189 497 051
 Singapore: 1 Raffles Place, #20-61 | One Raffles Place Tower 2 | 048616 | +65 6808 5574



www.exagrid.com

ExaGrid reserves the right to change specifications or other product information without notice. ExaGrid and the ExaGrid logo are trademarks of ExaGrid Systems, Inc. All other trademarks are the property of their respective holders. ©2019 ExaGrid Systems, Inc. All rights reserved.